

## L1 SERIES







### HEAVY-DUTY COMMERCIAL GRADE 1 LEVERSETS



#### Standard Features

- **Certification** ANSI A156.2, Series 4000, Grade 1, (800,000 cycles), UL listed for 3 hour door  
ANSI A117.1 American Disabilities Act (ADA)
- **Chassis** Cylindrical, zinc dichromate steel (corrosion resistance), freewheeling clutch  
(added security from hammer attacks), 2-1/8" bore, 1-3/8" - 2" door thickness
- **Trim** Non handed, solid cast with separate spring cage  
Thru bolted assembly, concealed mounting screws
- **Latch** 2-3/4" latch backset, latch bolt stainless steel with 1/2" throw  
1-1/8" x 2-1/4" square corner faceplate, 1" diameter housing
- **Strike** 1-1/4" x 4-7/8" ANSI ASA Strike standard
- **Cylinder** 6 pin solid brass Schlage "C" keyway standard  
Other keyways available upon request
- **Keys** Two nickel silver per lock
- **Warranty** Limited Lifetime, see page 2 for details

# L1 SERIES FUNCTION CHART

Function (ANSI)	Item No.	Outside / Inside	Function Description
Entrance (ANSI F81)	L1-KE-26D		<ul style="list-style-type: none"> <li>Latchbolt operated by lever from either side</li> <li>Outside lever locked by push button from inside</li> <li>Unlocked by key from outside</li> <li>When locked by push and turn from inside, key from outside or rotating lever retracts latch, does not unlock outside lever</li> </ul>
Storeroom (ANSI F86)	L1-ST-26D		<ul style="list-style-type: none"> <li>rotating inside lever</li> <li>Outside lever always fixed</li> </ul>
Classroom (ANSI F84)	L1-CL-26D		<ul style="list-style-type: none"> <li>Outside lever locked or unlocked by outside key</li> <li>Latchbolt operated by lever from each side.</li> <li>Egress always available by inside lever</li> </ul>
Passage (ANSI F75) Hall/Closet	L1-PS-26D		<ul style="list-style-type: none"> <li>Latchbolt operated by lever from either side at all times</li> </ul>
Privacy (ANSI F76) Bedroom/Bathroom	L1-PR-26D		<ul style="list-style-type: none"> <li>Latchbolt operated by lever either side</li> <li>Outside lever locked by push button on inside</li> <li>Unlocked by rotating inside lever, closing door or by emergency release on outside</li> </ul>
	L1-DMY-26D		<ul style="list-style-type: none"> <li>Pull lever one side</li> <li>No mechanical operation</li> <li>Latch operated by key in outside lever or</li> </ul>

## L1 SERIES ACCESSORIES

---

2-3/4" Guarded, 32D  
Various finishes upon request



- UL Listed latch bolt with or without deadlatch function
- 1/2" throw, 2-3/4" backset
- Fits 161 door prep (2-1/8" bore, 1" latch hole)

Cylinder, Schlage C, US26D



- Standard brass 6-pin SCC keyway
- Optional keyways available

ASA Strike  
Various finishes upon request



- For metal frames (1-3/4" x 4-7/8" x 3/32")

T Strike  
Various finishes upon request



- For wood frames (1-1/8" x 2-3/4" x 3/32")

T Strike  
Various finishes upon request



- For wood residential applications (1-5/8" x 2-1/4" x 3/32")

## L2 SERIES







### STANDARD-DUTY COMMERCIAL GRADE 2 LEVERSETS



#### Standard Features

- **Certification** ANSI A156.2, Series 4000, Grade 2, (400,000 cycles), UL listed for 3 hour door  
ANSI A117.1 American Disabilities Act (ADA)
- **Chassis** Cylindrical, zinc dichromate steel (corrosion resistance)  
1-3/8" - 1-3/4" door thickness - Fits standard 160/161 prep
- **Trim** Non handed  
Removable thru bolt available
- **Latch** 2-3/4" latch backset, latch bolt stainless steel with 1/2" throw  
1-1/8" x 2-1/4" square corner faceplate, 1" diameter housing
- **Strike** 1-1/4" x 4-7/8" ANSI ASA Strike standard
- **Cylinder** 6 pin solid brass Schlage "C" keyway standard  
Other keyways available upon request
- **Keys** Two nickel silver per lock
- **Warranty** 3 year limited

# L2 SERIES FUNCTION CHART

Function (ANSI)	Item No.	Outside / Inside	Function Description
Entrance (ANSI F82)	L2-KE-26D		<ul style="list-style-type: none"> <li>Latchbolt operated by lever from either side</li> <li>Outside lever locked by push button from inside</li> <li>Unlocked by key from outside</li> <li>When locked by push and turn from inside, key from outside or rotating lever retracts latch, does not unlock outside lever</li> </ul>
Storeroom (ANSI F86)	L2-ST-26D		<ul style="list-style-type: none"> <li>Latch operated by key in outside lever or rotating inside lever</li> <li>Outside lever always fixed</li> </ul>
Classroom (ANSI F84)	L2-CL-26D		<ul style="list-style-type: none"> <li>Outside lever locked or unlocked by outside key</li> <li>Latchbolt operated by lever from each side.</li> <li>Egress always available by inside lever</li> </ul>
Passage (ANSI F75) Hall/Closet	L2-PS-26D		<ul style="list-style-type: none"> <li>Latchbolt operated by lever from either side at all times</li> </ul>
Privacy (ANSI F76) Bedroom/Bathroom	L2-PR-26D		<ul style="list-style-type: none"> <li>Latchbolt operated by lever either side</li> <li>Outside lever locked by push button on inside</li> <li>Unlocked by rotating inside lever, closing door or by emergency release on outside</li> </ul>
	L2-DMY-26D		<ul style="list-style-type: none"> <li>Pull lever one side</li> <li>No mechanical operation</li> </ul>

## L2 SERIES ACCESSORIES

---

2-3/4" Guarded, 32D  
Various finishes upon request



- UL Listed latch bolt with or without deadlatch function
- 1/2" throw, 2-3/4" backset, 2-3/8" available
- Fits 160/161 door prep (2-1/8" bore, 1" latch hole)

Cylinder, Schlage C, US26D



- Standard brass 6-pin SCC keyway
- Optional keyways available

ASA Strike  
Various finishes upon request



- For metal frames (1-3/4" x 4-7/8" x 3/32")

T Strike  
Various finishes upon request



- For wood frames (1-1/8" x 2-3/4" x 3/32")

T Strike  
Various finishes upon request



- For wood residential applications (1-5/8" x 2-1/4" x 3/32")

---

## LD SERIES

### STANDARD-DUTY COMMERCIAL GRADE 2 DEADBOLTS

---





---

#### Standard Features

- **Certification** ANSI A156.2, Series 4000, Grade 2, (150,000 cycles)
- **Chassis** Tubular steel
- **Faceplate** 1" x 2-1/4" standard, packed with 1/8" filler for 1-1/8"
- **Deadbolt** 1" throw deadbolt with sturdy, all steel latch case and mechanism  
Latch and strike screws are 8-32 x 1" combination wood/machine
- **Cylinder Guard** 2-1/2" dia. Cylinder guard and metal insert, turns free with any removal attempt
- **Cylinder** Pick resistance solid brass 6 pin tumbler plug  
One piece solid brass housing for extra strength
- **Keys** Two nickel silver per lock
- **Warranty** 3 year limited

# LD SERIES FUNCTION CHART

Function (ANSI)	Item No.	Outside / Inside	Function Description
Single Cylinder (ANSI E0152)	LD-SGL-26D		<ul style="list-style-type: none"> <li>▪ Deadbolt operated by key outside, thumb turn inside</li> </ul>
Double Cylinder (ANSI 0142)	LD-DBL-26D		<ul style="list-style-type: none"> <li>▪ Deadbolt operated by key outside, key inside</li> </ul>