


LM SERIES






EXTRA HEAVY-DUTY COMMERCIAL GRADE 1 MORTISE



Standard Features

- **Certification** ANSI A156.13-1 80, Series 1000, Grade 1, UL listed for 3 hour door
ANSI A117.1 American Disabilities Act (ADA)
- **Lockcase** Heavy gauge zinc chromate steel lockcase, rocker type, brass, chrome plated stopworks, 1-3/4" door thickness, rust-proof 2-3/4" backset lock case
- **Front** 8" x 1-1/4" x 3/32" heavy gauge steel with wrought brass armored front attached by machine screws to lockcase front
- **Trim** Handed, forged brass levers with individual spring to prevent lever sag
Section trim standard with forged brass escutcheon trim available upon request
Escutcheon trim available upon request
- **Latch** Brass, chrome plated 3/4" latchbolt with anti-friction latch
1" throw, brass, chrome plated with hardened steel rollers dead bolt
- **Strike** 1-1/4" x 4-7/8" ANSI ASA Strike standard
- **Cylinder** 6 pin solid brass Schlage "C" keyway standard
Other keyways available upon request
- **Keys** Two nickel silver per lock
- **Warranty** Limited Lifetime, see page 2 for details

LM SERIES FUNCTION CHART

Function (ANSI)	Item No.	Outside / Inside	Function Description
Office (ANSI F04)	LM-KO-26D		<ul style="list-style-type: none"> Latchbolt operated by lever from either side except when outside lever is made inoperative by push button rocker When outside lever is locked, latchbolt may be retracted by key from outside or by rotating inside lever Auxiliary deadbolt latch
Entrance (ANSI F20)	LM-KE-26D		<ul style="list-style-type: none"> Latchbolt operated by lever from either side except when outside lever is made inoperative by push button rocker Deadbolt projected by key from outside and by thumbturn from inside Deadbolt retracted by key from outside. Both bolts retracted by inside lever (simultaneous retraction) Auxiliary deadbolt latch
Storeroom (ANSI F07)	LM-ST-26D		<ul style="list-style-type: none"> Latchbolt operated by key from outside or rotating inside lever Outside lever is always inoperative Egress always available by inside lever Auxiliary deadbolt latch
Classroom (ANSI F05)	LM-CL-26D		<ul style="list-style-type: none"> Latchbolt operated by lever from either side except when outside lever is locked from outside with key When outside lever is locked, latchbolt may be retracted by inside lever or outside lever when cylinder is unlocked Auxiliary deadbolt latch
Passage (ANSI F01)	LM-PS-26D		<ul style="list-style-type: none"> Latchbolt operated by lever either side at all times
Privacy (ANSI F02) (ANSI F19) (ANSI F22)	LM-PR-26D		<ul style="list-style-type: none"> Latchbolt operated by lever either side except when turnpiece projects deadbolt and locks outside lever Unlocked by turning inside lever or by using emergency key switch which retracts the deadbolt